

WS2 SERIES SNAP ACTION SWITCH

ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS



APPLICATIONS / MARKETS




HVAC



Electrical Housewares




Floor Care Appliances



White Goods



Vending Machines



Medical Equipment



RoHS

SPECIFICATIONS

Contact Rating: 01 = 2A @ 30VDC
2A @ 250VAC
Contact Resistance: 50mΩ MAX. (Initial)
Insulation Resistance: 100MΩ MIN. @ 500VDC
Dielectric Strength: 500VAC for 1 minute
Electrical Life: 100,000 Cycles MIN.
Mechanical Life: 500,000 Cycles MIN.
Operating Temperature: -25°C to 85°C
Operating Force: 183 gf MAX.
Circuit: SPDT
Moisture Protection: IP67
Agency Approvals: cURus

FEATURES & BENEFITS

- Multiple termination options
- Long cycle life
- IP67 rated
- UL Certified

PART NUMBER CONFIGURATOR

Series	Operating Temperature	Current Rating	Actuator	Operating Force	Termination	Circuit
WS2	085 - 85°C	01 - 2A @ 30VDC
2A @ 250VAC	00 - Pin Plunger	F183 - 183 gf	<input connect<br="" quick="" type="text" value="S1 - Solder Lug
C1 - 0.110"/> P1 - PCB Pin"/>	A - SPDT

Specifications subject to change without notice 8.3.2022



E-SWITCH®

www.e-switch.com

800.867.2717





1

WS2 SERIES SNAP ACTION SWITCH

BODY DIMENSIONS - SOLDER LUG

O.P. (MM)	F.P. (MM)
8.10~8.70	9.30 MAX

O.P. = OPERATING POINT
F.P. = FREE-POSITION



E-SWITCH®

www.e-switch.com

800.867.2717

2



ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS

WS2 SERIES SNAP ACTION SWITCH

BODY DIMENSIONS - QUICK CONNECT

O.P. (MM)	F.P. (MM)
8.10~8.70	9.30 MAX

O.P. = OPERATING POINT
F.P. = FREE-POSITION



E-SWITCH®




www.e-switch.com

800.867.2717

3



WS2 SERIES SNAP ACTION SWITCH

BODY DIMENSIONS - PCB PIN



O.P. (MM)	F.P. (MM)
8.10~8.70	9.30 MAX

O.P. = OPERATING POINT
F.P. = FREE-POSITION



E-SWITCH®

www.e-switch.com

800.867.2717

4

ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS